

FRAME ADHESIVE

It is used catalyzer for quick drying.



Highlights

- ▶ It dries much faster when compared to other adhesive.
- ▶ It is used for gluing textile materials to print frames.
- ▶ It is economical than sprays.
- ▶ It provides excellent adhesion even if high application and drying speed.



Printing Tips

- ▶ It has been manufactured to quick drying
- ▶ It sprays to application frames with special air spray apparatus.



Precautions

- ▶ Before usage, please stir the product well.
- ▶ Dispersible in water.
- ▶ It is packed in 3,8 kg plastic cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Physical and Chemical Properties



Appearance: Transparent, Red

Viscosity: 4.000-5.000 mPas

Density: 1,0 g/cm³

pH: 6.5-7.5

Boiling Point: >212°F

Additives



It should be used with catalyzer
(Catalyzer weight: appr. 20%)

Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

