



## HYBRID HM WHITE

## Product Information Bulletin

## Recommended Parameters

### HYBRID HM WHITE

Water-based printing paste where used to achieve an elastic, soft touching and white covering effect in textile printing. Does not dry during the print and block the screen.

#### Highlights

- If used correctly as advised, it does not during the print and block in the silk-screen
- Soft hand feel white for photographic prints
- Suitable for CMYK Printing
- Non Clogging White on high mesh counts
- It has high wash fastness.

#### Printing Tips

- It has been manufactured for high screen and thin templates
- It provides to soft hand feel white for photographic prints

#### Compliance

- Suitable to ecological standards.
- For Ecological Certifications, please visit [www.inknovators.com](http://www.inknovators.com)

#### Precautions

- Never use water to reduce the viscosity.
- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with water and sponge.
- Soluble in water.
- It is packed in 30kg and 60kg blue polyethylene cans.
- It is not explosive
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: [info@inknovators.com](mailto:info@inknovators.com)

#### Mesh

Counts: 77-120 mesh



#### Squeegee

Durometer: 70-80 Shore  
V type dr. blade



#### Cure Temperatures

320°F(160°C) for 1.5 minutes  
280°F(140°C) for 2 minutes



#### Additives

Do not use any additives that are not advised



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Clean Up

Water and sponge



#### Health & Safety

Please see: Safety Data Sheet

