



HYBRID RETARDER GEL

Product Information Bulletin

Recommended Parameters

HYBRID RETARDER GEL

It is a retarder - slows the drying time of acrylic prints.

Highlights

- If used correctly as advised, It does not dry during the print and block in the silk-screen
- It provides to easy work of products in silk-screen plate.
- It is an addivite used to slow down their drying time in the screen to all the hybrids inks
- It is added inside of the pigment paste and mixed well
- It is auxiliary material which provides to retard of printing paste

Printing Tips

It has been manufactured for silk-screen print

Precautions

- Soluble in water.
- Recomenended ratio is %5.
- It is packed in 10kg and 30kg blue polyethylene cans.
- It needs to be added inside of the hybrid inks and mixed well.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

