

HYBRID TB CLEAR

Product Information Bulletin

HYBRID TB CLEAR

It is a water based printing base used to achieve an elastic and soft touching effect in textile printing. It can be used as a transparent or can be coloured with Inknovators pigments.

🕮 Highlights

- If used correctly as advised, the dry-wet rubbing and washing fastness are high.
- ► It provides elastic and soft touch prints
- Self curable ink without any additives
- ► Please make the wash tests after 48 hours.

Printing Tips

It has been manufactured for elastic and proper surface printings

Compliance

Suitable to ecological standards

Precautions

- Never use water to reduce the viscosity.
- ► Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with water and sponge.
- Dispersible in water.
- ► It is packed in 30kg and 60kg blue polyethylene cans.
- ► It can be mixed with Hybrid TB White in any ratio.
- ► The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

Recommended Parameters

Counts: 43-62 mesh



Squeegee

Durometer: 55-60 Shore V type dr. blade



Cure Temperatures

302-320°F(150-160°C) for 1.5 mins Self curable in 48 hours



Additives



Do not use any additives that are not advised 1% Air Fix 1 could be added for speed up the self curing process



Shipping & Storage 41°F - 86°F (5°C - 30°C)



Clean Up Water and sponge



Health & Safety

Please see: Safety Data Sheet

