

NON-ELASTIC MATT WEISS

Water-based printing paste where used to achieve soft touching and white covering effect in textile printing. Doesn't dry during the print and block the screen

Highlights

- ▶ If used correctly as advised, has high wash fastness to dry-wet rubbing.
- ▶ It provides soft touch prints.
- ▶ Rubbing and washing tests should be applied 24 hours after curing

Printing Tips

- ▶ It has been manufactured for proper surface printings.

Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit www.inknovators.com

Precautions

- ▶ Never use water to reduce the viscosity.
- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with water and sponge.
- ▶ Soluble in water.
- ▶ It is packed in 5kg, 10kg, 20kg, 30kg, 60kg and 80kg polyethylene cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts: 43-77 mesh



Squeegee

Durometer: 50-70 Shore
V type dr. blade



Cure Temperatures

280°F(140°C) for 2 minutes
320°F(160°C) for 1,5 minutes



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Water and sponge



Health & Safety

Please see: Safety Data Sheet

