



PL CATALYST

Product Information Bulletin

Recommended Parameters

PL CATALYST

It is a phthalate free based catalyst

Highlights

- ▶ PL Catalyst increases wash fastness.
- ▶ It creates cross-link to fabric in thermal operations under the room temperature.
- ▶ It is an auxiliary material that improved to dry-wet crocking test and wash fastness.

Usage

- ▶ Before use, please stir the product well. Do not use any additives that are not advised.
- ▶ After adding to plastisol printings paste, it should be used in 24 hours, otherwise the printing paste can be damaged.

Compliance

- ▶ It is not suitable to ecological standards because it contains PVC.

Precautions

- ▶ It is packed in 1kg, 5kg, 10kg, 20kg plastic cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Recommended percentage

between 1-3%



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

