

### PU ANTIMIGRATION BASE

It is a water based barrier printing base.

#### Highlights

- ▶ It is prevent to contaminate base color's to print.
- ▶ It has extremely wash fastness.
- ▶ It provides to elastic and excellent migration barrier on dark colored

#### Printing Tips

- ▶ It is used for prevent to contaminate prints of polyester fabric & reactive printing fabric

#### Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit [www.inknovators.com](http://www.inknovators.com)

#### Precautions

- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ Soluble in water.
- ▶ It is packed in 5kg, 10kg, 20kg, 30kg and 60kg blue polyethylene cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: [info@inknovators.com](mailto:info@inknovators.com)

#### Fabric Types

Effective on polyester fabric and reactive printing fabric



#### Mesh

Counts: 43-77 mesh



#### Squeegee

Durometer: 50-70 Shore U type dr. blade



#### Cure Temperatures

320°F(160°C) for 1.5 minutes  
280°F(140°C) for 2 minutes



#### Additives

Do not use any additives that are not advised



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Clean Up

Water and sponge



#### Health & Safety

Please see: Safety Data Sheet

