

Hybrid Table Adhesive

General

Water based table adhesive

Advantages

- Hybrid Table Adhesive is economical than sprays.
- Suitable to ecological standards.

Applications

- Hybrid Table Adhesive is used for gluing textile materials to print tables.
- It is designed to strenght for pressure of low noise that is emulsion polymer for ready-to-use.
- It provides excellent adhesion even if in high application speed.
- Hybrid Table Adhesive has improved drying properties which are peeling, adhesion and cutting.

Usage

- It sprays to application tables with special air spray apparatus.
- It has low water strenght therefore Hybrid Table Adhesive can be used with warehouse labels that should be designed as hard and/or plastise (made from PVC, PE and PP film)
- Before use please stir this product well.
- Filtration should be advised with low power pump (>50 μ)

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30) $^{\circ}$ C /(+41)-(+86) $^{\circ}$ F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance

Liquid



Odor

Characteristic



Color

Milky



Viscosity

[(77 $^{\circ}$ F/25 $^{\circ}$ C) sp:7,rpm:20 Brookfield] :
50.000 – 90.000 [mPa.s]



Density

1,1 g/cm³ (25 $^{\circ}$ C/77 $^{\circ}$ F)



pH

7,0 – 8,0



Boiling Point

>100 $^{\circ}$ C (212 $^{\circ}$ F)



Solubility

Soluble with water



Explosion Hazard

It is not explosive



Packaging Information

Hybrid Table Adhesive is packed in
1/5/10/20/30 kg blue polyethylene
cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help. Printing performance and the quality may change with different company and application conditions. So please begin your printings serial process after completing your own trial tests.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 28 January 2026

Rev. No: 00

ALV KİMYA SANAYİ İÇ VE DIŞ TİCARET ANONİM ŞİRKETİ

Velimeşe OSB Mah. 2.Yanyol Cad.No:12 Ergene / TEKİRDAĞ

+90 282 676 42 05 info@alvkimya.com

TDS No: 041 Page 1/1