

ED White

General

It is a water based printing base that has high color and soft touching effect used by discharging the color of the dischargeable fabric in textile printing.

It can be used as a white or can be colored with pigments.

Advantages

- ED White has high wash resistance.
- ED White should be used with 5% Activator.
- PVC, formaldehyde free.
- Suitable to ecological standards.
- It is fixed at (320°F /160°C) for 2 minutes.
- It provides to soft-handfeel white color.

Applications

- ED White is used to make discharge prints without formaldehyde.

Usage

- It provides to print with the silk-screen that are made between 43-62 mesh.
- It can be mixed with EP 10 Clear in any ratio.
- 50 – 60 Shore U type should be used.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance

Pasta



Odor

Characteristic



Color

White



Viscosity

[(77°F/25°C) sp:7,rpm:20 Brookfield] :
90.000 – 105.000 [mPa.s]



Density

1,2 g/cm³ (25 °C/77 °F)



pH

8,0 – 8,5



Boiling Point

>100°C (212°F)



Solubility

Soluble with water



Explosion Hazard

It is not explosive



Packaging Information

ED White is packed in
1/5/10/20/30 kg blue polyethylene
cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help. Printing performance and the quality may change with different company and application conditions. So please begin your printings serial process after completing your own trial tests.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 28 January 2026

Rev. No: 00

ALV KİMYA SANAYİ İÇ VE DIŞ TİCARET ANONİM ŞİRKETİ

Velimeşe OSB Mah. 2.Yanyol Cad.No:12 Ergene / TEKİRDAĞ

+90 282 676 42 05 info@alvkimya.com

TDS No: 073 Page 1/1