



# RD Fixing Agent

## TECHNICAL DATA SHEET

---

### RD Fixing Agent

**General:** It is a fastness enhancing product.

#### Technical Details :

<b>Appearance</b>	: Paste
<b>Odor</b>	: Charateristic
<b>Color</b>	: Transparent
<b>pH</b>	: 7.0 - 8.0
<b>Density</b>	: 1,0 g/cm <sup>3</sup> (77 °F)
<b>Boiling Point</b>	: >212°F
<b>Solubility</b>	: Soluble in water

(Standards: for fastness tests - ISO 105-X10: 1993 / ISO 105-D01:2010 / ISO 105-B02:2013)

#### Advantages :

RD Fixing Agent increases all fastness of products which mixing it.

RD Fixing Agent provides extremely wash fastness. Suitable to ecological standards.

#### Applications :

RD Fixing Agent has been manufactured to obtain soft effected printings.

#### Usage :

RD Fixing Agent is an discharge print paste.

Recommended percentage : % 5 - 20

#### Packaging Information :

RD Fixing Agent is packed in 5 kg plastic cans.

#### Storage & Shelf Life :

Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30) °C/(+41)-(+86)°F of temperature.

It should be consumed within 2 years after the production date.



## **RD Fixing Agent**

### **TECHNICAL DATA SHEET**

---

**Important :**

*The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.*

*In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.*

*The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.*